

FD Series

The Most Reliable Premium Entry Level Real Time Series for Everyone



About

FD series is targeted at expanding DVR market. As the market is expanding from Professional to Consumer and into wider sectors, both price and feature oriented products are highly demanded in these days across different market sectors. FD series is designed to fulfill these various aspects of different market sectors. Highly affordable, reliable and usable DVR series to fulfill basic needs of DVR with the most satisfactions.

Specification

		FD02	FD04
Video	In	2 BNC	4 BNC
	Out	HDMI & VGA	
Audio	In	2 RCA	4 RCA
	Out	2 RCA(SPOT Audio), 1RCA	1RCA
CVBS	Out	2 BNC(SPOT Video)	1 BNC(SPOT Video)
Device	Sensor	3 TTL	4 TTL
	Alarm	2 OC(open collector)	4 OC(open collector)
	Serial	RS232 & RS485	
	USB	2	
Display	Speed	real time	
	Resolution	1920 x 1080	1920 x 1080
	Display	1, 4, PIP, Digital Zoom	
	Compression	H.264 & ADPCM	
Recording	Speed /Resolution	"60fps@Full HD(1080p) 60fps@HD(720p)"	"60fps@Full HD(1080p) 60fps@HD(720p)"
	Quality	Very High, High, Standard, Low	
	Mode	Time-lapse, Event, Time & Event, Emergency	
	Display	1, 4, Digital Zoom	
Playback	Search	Calendar, Event, Text-In, Go to Time	
	Playback	"Multi Channel Normal & Reverse Play,RW & FF (x2, x4, x8, x16, x32), Frame to Frame, Pause"	
Network	Interface	Ethernet (10/100/1000 Base)	
	Protocol	TCP/IP, HTTP, DHCP, ADSL(PPPoE), RTP/RTSP	
	Application	Live, Playback, Setup, Notification(Callback, E-Mail)	
	Web	Internet Explorer 7 or higher	
	Mobile	iPhone, Android phone, BlackBerry phone	
Storage		2 SATA HDD	
Backup		External HDD, External Memory	
Control		"Front Panel Button, USB Mouse,IR Remote Controller"	
OSD		Graphical User Interface	
Approval		FCC, CE, KC	
ROHS		ROHS Compliance	
Power Consumption		DC12V, 5A (60W)	
Operating Temperature		5°C ~ 40°C / 41°F ~ 104°F	
Operating Humidity		0% ~ 80%	
Dimension		340(W)x67(H)x265(D)mm / 13.39(W)x2.64(H)x10.43(D)inch	
Weight		2Kg / 4.4lb	

*Specification & Design are subject to change without prior notice

Features

- Triple Streaming / Digital Zoom
- Advanced User Authority Level
- Max 128ch CMS Client S/W
- POS (Text Insert Function)

Dimension

